FOTHERGILL COATED FABRICS LTD

PRODUCT SPECIFICATION

04-004/2D

Metal Detectable, PTFE Coated Glass Fabric

Properties	Values		Test Method
Thickness	mm	0.100	ASTM D1777
Weight	g/m^2	200	BS 3424: Part 3
Colour		Black	
PTFE	%	75	BS 3424: Part 3
Adhesive Weight	g/m^2	55	BS 3424: Part 3
Warp Tensile Strength	N/5cm	700	EN ISO 1421
Warp Tear Resistance	N	16	EN ISO 9073.4
Surface Resistance @ 1000V	Ohms/Sq	Insulative	ASTM D4496-98
Peel Adhesion	N/25mm	10	EN ISO 8510-2
Typical Temperature Range	°C	-72 to +260	

This product complies wih European Union Regulation (EC) 1907/2006 (REACH) and does not contain Substances of Very High Concern (SVHC). This material does not contain banned substances as described in the RoHS directive and will not affect RoHS compliance



Note: The Nominal values are typical and not intended as a specification and should be considered as a guide only. Contact our sales team with the details of your application. Fothergill Coated Fabrics reserves the right to alter any elements quoted in the above specification without prior notice. The product's suitability for all applications is at the user's discretion, samples for evaluation are available on request.